

Superflat Screed TS 6000

Equipped with state-of-the-art automatic laser system for accurate leveling, high productivity and operator comfort. Machine head disperses the concrete, removing excess and vibrating in one movement. Complies with confined space health and safety requirements with catalytic convertor fitted as standard.

Flatter, faster concrete laying

Advantages

- Automatic laser control system
- Increased daily productivity
- Improved concrete levelness
- Rotating & vibrating screed head
- Hydraulic washer
- Reduce unskilled manual labour
- Access code touchscreen control
- Easy to transport
- Customised to client's requirements
- Easy to maintain and service
- Foam filled wheels
- Automatic throttle
- LCD display
- Standard parts/ components
- Improved operator visibility
- 3D ready



Specifications subject to change without notice **Non contractual photo**

Technical description

Specifications	
Width	2.2 m
Working width	4.30 m
Transport length	8.40 m
Height	2.75 m
Weight	11 tons
Boom reach	6.3 m
Steering	2-4 wheels / Crab
Transport dimension	Standard
Screed head width	3.80 m
Slew	360°
Laser system	Topp & Screed SFS 2.0
Master valve and pump	Sauer Danfoss

Engine	
Brand	HATZ
Model	4H50TICD
Emission compliance	Stage V
Power	55 Kw @ 2800 RPM
Torque	240 nm @ 1600 - 2600 RPM
Fuel	Diesel
Fuel Tank capacity	100L
Oil Tank capacity	140L
Built in antifreeze dispenser	18L

Options	
Eco oil	On request
Seat Heating	On request
3D ready	On request
Screed -head 4.2M	On request
Additional LED lighting	On request
GPS tracking	On request
Skip float on Screed-head	On request

Features	
Catalytic convertor - DOC	As standard
Diesel particle filter	As standard
Central greasing system	As standard
High pressure washer	As standard
Seat protection	As standard
Screen protection	As standard